

Electric strikes provide remote release of a locked door. They allow the door to be opened without retracting the latch-bolt. This occurs by the release of the electric strike lip (sometimes called a keeper or gate). When the door closes the beveled latchbolt rides over the lip and falls into the strike pocket. A door can be set either as Fail Safe (loss of electrical power opens the door) or Fail Secure (loss of electrical power locks the door). PCSC provides a variety of high-quality strikes for the use in any installation. PCSC offers three different models of strikes in a variety of sizes and alloys, for the use in variety environments. Though each strike is by default sold as 12VDC in Fail Secure format, each strike has the option of being ordered in Fail Safe format and/or in 24VDC format. Designed for dependability and ease of installation, each strike allows concernfree use in any access control environment.

SPECIFICATION

Dimensions	250 X 25 X 31 Mm
Voltage	12V
Current	400Ma / 12Vdc
Face Plates	Steel (Painted), Length (250Mm)
Options	Saf- Fail Safe 24- 24Vdc

FEATURES

- Options available for fail-safe (upon power failure, lock opens great for stairwells and wherever emergency egress is a concern) or fail-secure (upon power failure, lock remains engaged). Our locks come standard as fail - secure with fail-safe optional.
- Flush mounted.
- Dry contact sensor for door condition indication (can be hooked up to a indication light or buzzer).
- Functions on DC current for quiet operation.
- 12 volt or 24 volt option.



DIMENSIONS

